

Manual Engine Control Panel

STANDARD FEATURES



ENGINE & GENERATOR CONTROLS

Enclosure: IP66 and UL-50/c-UL listed, High impact, UV resistant polycarbonate materials. Stainless steel locking latch. Grey enclosure and opaque lid to withstand high temperature direct sunlight exposure. Instruments mounted on rigid aluminum faceplate.

VDO Instrumentation: 3-3/8" 3000 RPM tachometer with hourmeter, 2-1/16" 150 psi oil pressure, 250F water temperature, voltmeter.

Available in 12V or 24V versions, Panel protected by 15A DC main breaker.

4 Position key switch, pre-off-ignition-start. Oil pressure safety override switch for engine cranking.

Cole-Hersee 85A continuous duty start solenoid (shipped loose)

Safety shutdown circuit for Low Oil Pressure, High Water Temperature and other switch to ground fault circuits with Safety Shutdown LED.

Panel also Includes: 15ft. 9 pin quick disconnect engine harness, 1/8" VDO oil pressure sender/switch combo, 1/2" water temperature sender/switch combo, 4 vibration isolators.

Dimensions 8.50" (w) x 10.50" (h) x 7.50" (d) (not including hinge and latch)

P11-IND

N4X Industrial Engine Panel for Mechanical Engines

Complete Panel Kit



Included Engine Harness, Oil and Temperature Senders, Start Solenoid, Vibration Isolators.



How to Order: P11- IND-_____

1=12VDC 2=24VDC

National Marketing and Distribution by Davidson Sales Co.

839 Bill France Blvd., Daytona Beach, FL 32117

Phone: (386)274-2079 Fax: (386)274-2279 www.davidsonsales.com