

Safety Data Sheet

Issue Date:	01-Jan-2008	Revision Date:	14-Jul-2015		Vers	ion 1
		1. IDENT	IFICATION			
<u>Product Ider</u> Product Nan		DEE-ZOL LIFE				
Other means SDS #	s of identification	BELL-070				
UN/ID No		UN1268				
<u>Recommenc</u> Recommenc		and restrictions on use Fuel oil additive.				
Details of th Manufacture Bell Performa 1340 Bennet Longwood, F	ance Inc t Drive	data sheet				
Company Pl	<u>Telephone Number</u> hone Number Telephone (24 hr)	407-831-5021 INFOTRAC 1-352-323-35 1-800-535-5053 (North A				
		2. HAZARDS II	DENTIFICATION			
Appearance	Clear amber liquid	Physical S	tate Liquid		Odor Ar	omatic
<u>Classificatio</u>	on_					
Acute toxicity	/ - Inhalation (Dusts/Miste	5)		Category 4		
Skin corrosio		,		Category 2		
	damage/eye irritation			Category 2		
Germ cell mu				Category 1B		
Carcinogenic				Category 1B		
	et organ toxicity (repeate	d exposure)		Category 1		
Aspiration to:				Category 1		
Flammable L				Category 3		
Hazards Not	t Otherwise Classified (Iful if swallowed	HNOC)				
<u>Signal Word</u> Danger	<u>I</u>					

Hazard Statements

Harmful if inhaled Causes skin irritation Causes serious eye irritation May cause genetic defects May cause cancer Causes damage to organs through prolonged or repeated exposure May be fatal if swallowed and enters airways Flammable liquid and vapor



Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Use only outdoors or in a well-ventilated area Wash face, hands and any exposed skin thoroughly after handling Wear eye/face protection Do not breathe dust/fume/gas/mist/vapors/spray Do not eat, drink or smoke when using this product Keep away from heat/sparks/open flames/hot surfaces. — No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof equipment Use only non-sparking tools

Precautionary Statements - Response

Take precautionary measures against static discharge

If exposed or concerned: Get medical advice/attention IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower Wash contaminated clothing before reuse If skin irritation occurs: Get medical advice/attention IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do not induce vomiting IN CASE OF FIRE: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Please also refer to subsequent sections of this SDS for additional information regarding the components of this product.

Chemical Name	CAS No	Weight-%
Mineral Spirits	8052-41-3	Proprietary
Ethylene Glycol Monobutyl Ether	111-76-2	Proprietary
Naphtha (petroleum), heavy aromatic	64742-94-5	Proprietary
1,2,4 Trimethylbenzene	95-63-6	Proprietary
Naphthalene	91-20-3	Proprietary

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

First Aid Measures			
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.		
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. If skin irritation persists, call a physician.		
Inhalation	Remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a POISON CENTER or doctor/physician.		
Ingestion	Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Immediately call a poison center or doctor/physician.		
Most important symptoms and effe	ects		
SymptomsMay cause eye irritation. Exposed individuals may experience eye tearing, redness and discomfort. May cause respiratory irritation. Prolonged or repeated contact may cause skin irritation. Prolonged breathing of vapors may cause nausea, headache, weakness and/or dizziness. May cause nausea, vomiting and/or diarrhea if ingested. Aspiration may occur during swallowing or vomiting and cause lung damage. For Chronic Exposure. May aggravate pre-existing skin conditions. May cause central nervous system effects.			
Indication of any immediate medical attention and special treatment needed			
Notes to Physician	Treat symptomatically.		
5. FIRE-FIGHTING MEASURES			

Suitable Extinguishing Media

Carbon dioxide (CO2). Dry chemical. Foam.

Unsuitable Extinguishing Media Water may be ineffective, but can be used to protect firefighters and cool containers.

Specific Hazards Arising from the Chemical

Flammable liquid and vapor. Vapors are heavier than air and may accumulate in low areas or areas inadequately ventilated. Vapors may also travel along the ground to be ignited at location distant from handling site; flashback of flame to handling site may occur. Never use welding or cutting torch on or near drum (even empty), because product (even just residue) can ignite explosively.

Hazardous Combustion Products Carbon monoxide. Carbon dioxide (CO2).

Sensitivity to Static Discharge Take precautionary measures against static discharge.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Remove all sources of ignition. Observe all personal protection equipment recommendations described in Sections 5 & 8.
Environmental Precautions	Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. See Section 13: DISPOSAL CONSIDERATIONS. See Section 12 for additional Ecological Information.
Methods and material for containn	nent and cleaning up
Methods for Containment	Prevent further leakage or spillage if safe to do so.
Methods for Clean-Up	Use clean non-sparking tools to collect absorbed material. Take up with sand or other non-combustible absorbent material and place into containers for later disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Use personal protection recommended in Section 8. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Use spark-proof tools and explosion-proof equipment. Ground/bond container and receiving equipment. Take precautionary measures against static discharges. Do not breathe vapors or spray mist. Wash face, hands, and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep container tightly closed and store in a cool, dry and well-ventilated place. Store away from ignition sources and incompatible materials. Store locked up.
Incompatible Materials	Strong oxidizing agents. Strong acids. Strong bases. Amines.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Mineral Spirits 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³
Ethylene Glycol Monobutyl Ether 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³
1,2,4 Trimethylbenzene 95-63-6	-	-	TWA: 25 ppm TWA: 125 mg/m ³
Naphthalene 91-20-3	TWA: 10 ppm S*	TWA: 10 ppm TWA: 50 mg/m ³ (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m ³ (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m ³	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m ³ STEL: 15 ppm STEL: 75 mg/m ³

Appropriate engineering controls

Engineering Controls	Apply technical measures to comply with the occupational exposure limits. Eyewash
	stations. Showers.

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Chemical safety goggles/faceshield.
Skin and Body Protection	Suitable protective clothing. Impervious gloves such as nitrile are recommended for operations which may result in prolonged or repeated skin contact.
Respiratory Protection	Ensure adequate ventilation, especially in confined areas. In case of inadequate ventilation wear respiratory protection.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Take off all contaminated clothing and wash it before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Appearance Color	Liquid Clear amber liquid Clear amber	Odor Odor Threshold	Aromatic Not determined
<u>Property</u> pH Melting Point/Freezing Point Boiling Point/Boiling Range	<u>Values</u> Not determined Not determined Not determined	<u>Remarks • Method</u>	
Flash Point Evaporation Rate Flammability (Solid, Gas) Upper Flammability Limits Lower Flammability Limit Vapor Pressure Vapor Density	56.66 °C / 134 °F Not determined Not determined Not determined Not determined Not determined Not determined	Pensky-Martens Closed Cup (PMCC)	
Specific Gravity	0.917	(1=Water)	

Water Solubility
Solubility in other solvents
Partition Coefficient
Auto-ignition Temperature
Decomposition Temperature
Kinematic Viscosity
Dynamic Viscosity
Explosive Properties
Oxidizing Properties
Density

Insoluble in cold water Not determined 7.64 lbs/gal

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Keep out of reach of children. Keep away from sources of ignition such as heat, sparks or open flames.

Incompatible Materials

Strong oxidizing agents. Strong acids. Strong bases. Amines.

Hazardous Decomposition Products

Carbon monoxide. Carbon dioxide (CO2).

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	
Eye Contact	Causes serious eye irritation.
Skin Contact	Causes skin irritation.
Inhalation	Harmful if inhaled.
Ingestion	May be fatal if swallowed and enters airways. May be harmful if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Ethylene Glycol Monobutyl Ether 111-76-2	= 470 mg/kg (Rat)	= 99 mg/kg (Rabbit)	= 450 ppm (Rat)4 h
Naphtha (petroleum), heavy aromatic 64742-94-5	> 5000 mg/kg (Rat)	>2 mL/kg (Rabbit)	> 590 mg/m³ (Rat)4 h
1,2,4 Trimethylbenzene 95-63-6	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat)4 h
Naphthalene 91-20-3	= 490 mg/kg (Rat) = 1110 mg/kg (Rat)	> 20 g/kg (Rabbit)= 1120 mg/kg (Rabbit)	> 340 mg/m ³ (Rat)1 h

Information on physical, chemical and toxicological effects

Symptoms

Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity

May cause cancer.

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethylene Glycol Monobutyl	A3	Group 3		
Ether				
111-76-2				
Naphthalene	A3	Group 2A	Reasonably Anticipated	Х
91-20-3				

Legend

 ACGIH (American Conference of Governmental Industrial Hygienists)

 A3 - Animal Carcinogen

 IARC (International Agency for Research on Cancer)

 Group 2A - Probably Carcinogenic to Humans

 Group 3 IARC components are "not classifiable as human carcinogens"

 NTP (National Toxicology Program)

 Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

 OSHA (Occupational Safety and Health Administration of the US Department of Labor)

 X - Present

 STOT - repeated exposure
 Causes damage to organs through prolonged or repeated exposure.

 Aspiration hazard
 May be fatal if swallowed and enters airways.

Numerical measures of toxicity

Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
Ethylene Glycol Monobutyl		1490: 96 h Lepomis		1000: 48 h Daphnia magna
Ether		macrochirus mg/L LC50		mg/L EC50 1698 - 1940: 24
111-76-2		static 2950: 96 h Lepomis		h Daphnia magna mg/L
		macrochirus mg/L LC50		EC50
Naphtha (petroleum), heavy	2.5: 72 h Skeletonema	41: 96 h Pimephales		0.95: 48 h Daphnia magna
aromatic	costatum mg/L EC50	promelas mg/L LC50 1740:		mg/L EC50
64742-94-5		96 h Lepomis macrochirus		
		mg/L LC50 static 45: 96 h		
		Pimephales promelas mg/L		
		LC50 flow-through 19: 96 h		
		Pimephales promelas mg/L		
		LC50 static 2.34: 96 h		
		Oncorhynchus mykiss mg/L		
		LC50		
1,2,4 Trimethylbenzene		7.19 - 8.28: 96 h Pimephales		6.14: 48 h Daphnia magna
95-63-6		promelas mg/L LC50		mg/L EC50
		flow-through		

Naphthalene		5.74 - 6.44: 96 h Pimephales	2.16: 48 h Daphnia magna
91-20-3	costatum mg/L EC50	promelas mg/L LC50	mg/L LC50 1.96: 48 h
		flow-through 1.6: 96 h	Daphnia magna mg/L EC50
		Oncorhynchus mykiss mg/L	Flow through 1.09 - 3.4: 48 h
		LC50 flow-through 0.91 -	Daphnia magna mg/L EC50
		2.82: 96 h Oncorhynchus	Static
		mykiss mg/L LC50 static	
		1.99: 96 h Pimephales	
		promelas mg/L LC50 static	
		31.0265: 96 h Lepomis	
		macrochirus mg/L LC50	
		static	

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
Ethylene Glycol Monobutyl Ether	0.81
111-76-2	
Naphtha (petroleum), heavy aromatic	2.9 - 6.1
64742-94-5	
1,2,4 Trimethylbenzene	3.63
95-63-6	
Naphthalene	3.3
91-20-3	

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated Packaging	Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Naphthalene	U165	Included in waste streams:		U165
91-20-3		F024, F025, F034, F039,		
		K001, K035, K060, K087,		
		K145		

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Naphthalene			Toxic waste	
91-20-3			waste number F025	
			Waste description:	
			Condensed light ends, spent	
			filters and filter aids, and	
			spent desiccant wastes from	
			the production of certain	
			chlorinated aliphatic	
			hydrocarbons, by free radical	
			catalyzed processes.	
			These chlorinated aliphatic	
			hydrocarbons are those	
			having carbon chain lengths	
			ranging from one to and	
			including five, with varying	
			amounts and positions of	
			chlorine substitution.	

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Naphthalene	Toxic
91-20-3	

14. TRANSPORT INFORMATION

<u>Note</u>	Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances. Based on package size, product may be eligible for limited quantity exception.
<u>DOT</u> UN/ID No Proper Shipping Name Hazard Class Packing Group	In containers of 119 gallons capacity or less this product is not regulated by DOT UN1268 Petroleum products, n.o.s. (Aliphatic Hydrocarbons) 3 III
IATA_ UN/ID No Proper Shipping Name Hazard Class Packing Group	UN1268 Petroleum products, n.o.s. (Aliphatic Hydrocarbons) 3 III
IMDG UN/ID No Proper Shipping Name Hazard Class Packing Group Marine Pollutant	UN1268 Petroleum products, n.o.s. (Aliphatic Hydrocarbons) 3 III This material may meet the definition of a marine pollutant

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL	NDSL	EINECS	ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Mineral Spirits	Present	Х		Present		Present	Х	Present	Х	Х
Ethylene Glycol Monobutyl Ether	Present	Х		Present		Present	Х	Present	Х	Х
Naphtha (petroleum), heavy aromatic	Present	Х		Present		Present	Х	Present	Х	Х
1,2,4 Trimethylbenzene	Present	Х		Present		Present	Х	Present	Х	Х
Naphthalene	Present	Х		Present		Present	Х	Present	Х	Х

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Naphthalene	1 lb		RQ 1 lb final RQ
91-20-3			RQ 0.454 kg final RQ

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Ethylene Glycol Monobutyl Ether - 111-76-2	111-76-2	Proprietary	1.0
1,2,4 Trimethylbenzene - 95-63-6	95-63-6	Proprietary	1.0
Naphthalene - 91-20-3	91-20-3	Proprietary	0.1

CWA (Clean Water Act)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Naphthalene	100 lb	Х	Х	Х

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65	
Naphthalene - 91-20-3	Carcinogen	

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Mineral Spirits 8052-41-3	Х	X	Х
Ethylene Glycol Monobutyl Ether 111-76-2	Х	X	Х
1,2,4 Trimethylbenzene 95-63-6	Х	X	Х
Naphthalene 91-20-3	Х	X	Х

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazards 2	Flammability 2	Instability 0	Special Hazards Not determined
HMIS	Health Hazards Not determined	Flammability Not determined	Physical Hazards Not determined	Personal Protection Not determined
Issue Date: Revision Date: Revision Note:	01-Jan-2008 14-Jul-2015 New format			

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet