

DSEE800

ENGINE CONTROLLER

FEATURES

The DSEE800 is an easy to use engine controller designed to provide flexible control with built in monitoring and protection. The DSEE800 is compatible with both electronic and non-electronic diesel engines and fully configurable for a wide range of applications such as engine driven pumps, compressors, hydraulic power packs and off highway machinery.

Control of the application can be achieved both automatically and manually with engine start, speed and clutch control all built in. The monitoring and configuration of system variables allows the controller to start and stop the engine, increase and decrease engine speed as the output demands and program ramping for loading/unloading of the engine.

With the built in PLC editor the controller is fully flexible and can be adjusted to meet many different needs, providing the user with the ability to achieve special operating modes which are unique to their machine and application. A range of comprehensive communication and system expansion options ensures that the user can extend the input and output capability and communicate with other devices or systems offering further advanced and high level use in very demanding applications. On board event, data logging and trending makes it possible to determine preventative maintenance and improved performance criteria for the machine.

Using the DSE Configuration Suite PC Software the controller is easy to use and configure which allows alteration of operating parameters, sequences, timers and alarms.

ENVIRONMENTAL TESTING STANDARDS

ELECTRO MAGNETIC COMPATIBILITY

BS EN 61000-6-2
EMC Generic Immunity Standard for the Industrial Environment
BS EN 61000-6-4
EMC Generic Emission Standard for the Industrial Environment

ELECTRICAL SAFETY

BS EN 60950
Safety of Information Technology Equipment, including Electrical Business Equipment

TEMPERATURE

BS EN 60068
Ab/Ae Cold Test -30°C
BS EN 60068-2-2
Bb/Be Dry Heat +70°C

VIBRATION

BS EN 60068-2-6
Ten sweeps in each of three major axes
5Hz to 8Hz @ +/-7.5mm, 8Hz to 500Hz @ 2gn

HUMIDITY

BS EN 60068-2-30
Db Damp Heat Cyclic 20/55°C @ 95% RH
48 Hours
BS EN 60068-2-78
Cab Damp Heat Static 40°C @ 93% RH
48 Hours


SHOCK

BS EN 60068-2-27
Three shocks in each of three major axes
15gn in 11mS

DEGREES OF PROTECTION PROVIDED BY ENCLOSURES

BS EN 60529
IP65 - Front of module when installed into the control panel with the supplied sealing gasket.

COMPREHENSIVE FEATURE LIST TO SUIT A WIDE VARIETY OF ENGINE APPLICATIONS



DSEE800

ENGINE CONTROLLER

FEATURES



KEY FEATURES

- Built-in governor control
- Automatic speed control
- Manual speed control via push buttons, digital input or analogue input
- Automatic speed ramping
- Flexible automatic start control
- Clutch control
- 4-Line back-lit LCD text display
- Multiple display languages
- Five key menu navigation
- Front panel editing with PIN protection
- Customisable status screens
- Power save off mode
- Configurable digital inputs (11)
- Configurable ratiometric inputs (12)
- Configurable DC outputs (4)
- Configurable volt-free outputs (2)
- Configurable PWM outputs (4)
- Configurable timers and alarms
- 3 configurable maintenance alarms
- Multiple date and time engine scheduler
- Configurable event log (250)
- CAN engine support
- Advanced Integral PLC editor
- CAN, Magnetic Pick-up or tachometer speed sensing
- Fuel usage monitor and low fuel alarms
- Charge alternator failure alarm
- Manual fuel pump control
- "Protections disabled" feature
- LED and LCD alarm indication
- USB connectivity
- Backed up real time clock
- Fully configurable via DSE Configuration Suite PC software
- User selectable RS232, RS485 & Ethernet communications
- Modbus RTU & TCP support
- User configurable MODBUS pages
- Advanced SMS control and fault messaging (additional GSM modem required)
- Start & stop capability via SMS messaging
- Additional display screens to help with modem diagnostics
- DSENet® expansion compatible
- Data logging and trending

KEY BENEFITS

- 132 x 64 pixel ratio display for clarity
- Real-time clock provides accurate event logging
- Set maintenance periods can be configured to maintain optimum engine performance
- Ethernet communications provides built in advanced remote monitoring.
- Can be integrated into remote monitoring systems
- Increased input and output expansion capability via DSENet®
- Licence-free PC software
- IP65 rating (with supplied gasket) offers increased resistance to water ingress
- Advanced PLC editor allows user configurable functions to meet application requirements.

RELATED MATERIALS

TITLE	PART NO'S
DSEE800 Installation Instructions	053-090
DSEE800 Operator Manual	057-202
DSEE800 PC Configuration Suite Manual	057-203

DEEP SEA ELECTRONICS PLC UK

Highfield House, Hunmanby Industrial Estate, Hunmanby YO14 0PH
TELEPHONE +44 (0) 1723 890099 **FACSIMILE** +44 (0) 1723 893303
EMAIL sales@deepseapl.com **WEBSITE** www.deepseapl.com

DEEP SEA ELECTRONICS INC USA

3230 Williams Avenue, Rockford, IL 61101-2668 USA
TELEPHONE +1 (815) 316 8706 **FACSIMILE** +1 (815) 316 8708
EMAIL sales@deepseausa.com **WEBSITE** www.deepseausa.com

SPECIFICATION

DC SUPPLY

CONTINUOUS VOLTAGE RATING
 8 V to 35 V continuous

CRANKING DROPUTS

Able to survive 0 V for 50 mS, providing supply was at least 10 V before dropout and supply recovers to 5 V. This is achieved without the need for internal batteries.

MAXIMUM OPERATING CURRENT

510 mA at 12 V, 238 mA at 24 V

MAXIMUM STANDBY CURRENT

226 mA at 12 V, 107 mA at 24 V

MAXIMUM OFF MODE CURRENT

180 mA at 12 V, 86 mA at 24 V

CHARGE FAIL/EXCITATION RANGE

0 V to 35 V

INPUTS

DIGITAL INPUTS A to K

Configurable as:
 Positive switching
 Negative switching

RATIOMETRIC INPUT A

Configurable as:
 Negative switching digital input
 0 V to 10 V
 4 mA to 20 mA
 0 Ω to 480 Ω

RATIOMETRIC INPUTS B to L

Configurable as:
 Negative switching digital input
 0 V to 10 V
 4 mA to 20 mA
 0 Ω to 1920 Ω

OUTPUTS

DC OUTPUT A (FUEL) & B (START)

10 A short term,
 5 A continuous at supply voltage

VOLT-FREE OUTPUTS C & D

5 A DC at 35 V DC
 8 A AC at 250 V AC

DC OUTPUTS E, F, G & H

2 A DC at supply voltage

PWM OUTPUTS I, J, K & L

4 A at supply voltage
 20 Hz to 250 Hz

PULSE PICK-UP

VOLTAGE RANGE
 ±0.5 V to 60 V RMS
 Fully isolated

FREQUENCY RANGE

10,000 Hz (max)

BUILT-IN GOVERNOR CONTROL

MINIMUM LOAD IMPEDANCE

1000 Ω
 Fully isolated

GAIN VOLTAGE

0 V to 10 V DC

OFFSET VOLTAGE

±10 V DC

DIMENSIONS

OVERALL

240 mm x 172 mm x 57 mm
 9.4" x 6.8" x 2.2"

PANEL CUTOUT

220 mm x 160 mm
 8.7" x 6.3"

MAXIMUM PANEL THICKNESS

8 mm
 0.3"

OPERATING TEMPERATURE RANGE

-40 °C to +80 °C

STORAGE TEMPERATURE RANGE

-40 °C to +85 °C