



SPECIFICATIONS:

MATERIALS: RIBBED ELASTOMERIC FACE SHEETS, ALTERNATE HIGH AND LOW RIBS, 3 PER INCH,
BONDED TO 1/2" SOUND/VIBRATION ABSORBING PAD.

THICKNESS: 1"
RECOMMENDED LOADING: 5-60 P.S.I.
DEFLECTION: 0.025" TO 0.18"

NOTES:

1) AVAILABLE IN 36" X 36" SHEETS AND ALSO IN SMALLER SIZES CUT TO ORDER.

SIZE	LOAD RANGE
2 X 2	20 - 240
3 X 3	45 - 540
4 X 4	80 - 960
5 X 5	125 - 1500
6 X 6	180 - 2160
8 X 8	320 - 3840
9 X 9	405 - 4860



OTHER MATERIALS, COMPOUNDS OR FINISHES WITH EQUAL OR SUPERIOR PROPERTIES MAY BE SUBSTITUTED AS THEY BECOME AVAILABLE.

CERTIFIED FOR

PURCHASER — — — — —
 ORDER NO. — — — — —
 PROJECT — — — — —
 — — — — —

**MODEL: NRC
PAD ISOLATOR**

SCALE NONE
 DATE

DWG. NO.

P-1020

REV.

4

06/05