

Custom Remote Annunciator

STANDARD FEATURES

- Panelsource annunciator panel for use with Deep Sea 73X0, 74X0, 86X0, and 87X0 controllers.
- Built around the Deep Sea 2548 LED Expansion Module with 8 red LED's, audible horn, and text card insert.
- 16 LED version - modules are pre-wired together with power and data connection between modules, including wired 120 ohm termination resistor
- Module requires 12-24VDC nominal power and Belden 9841 or equivalent 120 ohm twisted pair communication cable. Up to 1000M distance from host controller using Belden 9841. Davidson Sales stocks Belden 9841—Inquire with sales.
- Enclosure: Type 1, Enamel coated steel. Faceplate: ABS UV resistant faceplate.



ENGINE & GENERATOR CONTROLS

P6-08-DS & P6-16-DS

P6-8-DS Flush



P6-16-DS Wall

- NFPA 110 Level 1 pre-programming available on P6-16-DS
- LED indication conditions field programmable through host controller using a PC and Deep Sea Configuration Suite Software.

Dimensions 8.00" (w) x 10.00" (h)
x 4.25" (d) **P6-08-DS (Wall Mount)**

Dimension 9.50" (w) x 11.50" (h)
x 4.25" (d) **P6-08-DS-F (Flush Mount)**

Dimensions 12.00" (w) x 10.00" (h)
x 4.25 (d) **P6-16-DS (Wall Mount)**

Dimensions 13.50" (w) x 11.50" (h)
x 4.25" (d) **P6-16-DS-F (Flush Mount)**

Dimensions

Na-

tional